

HERITAGE COLLECTION

Sash Windows



Standard Specification

- 133mm Featured Outerframe
 - Putty Line 3 Chamber Slim Top Sash**
 - Putty Line 3 Chamber Large Bottom Sash
 - 147mm Cill Profile
 - Black Concealed Gaskets
 - Balance Retaining Clips
 - White Tilt Latch Knobs to Bottom Sashes**
 - White Locking Cam, CC2 with 2 stage keep**
 - Aluminium Bead Incorporating Lift Handle
 - 4:16:4 Low Emissivity Glass
 - White Spacer Bars
 - Cill Gaskets
 - Access Slots
 - Ultralift balances (10 year warranty)**
 - Concealed drainage
 - Tilt in for easy cleaning**
 - Ovolo Beading Internally
- ** Depending on size and weight of sash

System U Value 1.95W/m²K

Optional Extras

- 2 No. White or Brass Effect Limit Stops, LS5
- Plant On Decorative Horns
- Trickle Vents in Sash Only
- 2 Piece Projecting Cills (27/62/102/142mm projection)
- Internal 18mm Georgian or Plant On External Only
- Fixing Lugs
- Bays Cills, Posts & Trims
- Arched Head
- Sash Secure[®] Upgrade
- Sashminder Magnetic Locking Device
- U Value Upgrades Available

N.B. Due to continued improvements of our products we reserve the right to alter specifications without notice.



Features and Benefits

Internal Georgian Bar

For easier cleaning of glass.

Balance Retaining Clip (Exclusive)

Balance is held into place in the balance shoe ensuring it will not become detached.

Cill Pads

Ensures seal between bottom of jambs and cills, to prevent leaks.

Continuous cill on all multilight windows

Cills do not have to be butted together, meaning no on site assembly and no water ingress.

BBA

The first manufacturer of vertical sliders to have system status testing to BBA endurance standards.

Slim top sash/large lower sash**

Gives equal glass sizes, achieving a balanced and traditional appearance.

Spacer bars in a choice of colours

All sashes internally glazed

Units cannot be removed from the outside giving the homeowner added peace of mind.

White or Brass Effect Fittings

Fully suited window fittings giving your client more choice.

Two part lift in/out pivot bars

Allows simple removal of sashes for easier on site handling.

Plant On Decorative horns

Allows like for like replacement.

2 key locking limit stops LS5

Restricts initial opening to 100mm on both sashes for child safety. Available in white or brass effect.

Trickle ventilator in sash

To comply with new building regulations.

Foam baffles (Exclusive)

Reduces the possibility of draughts.

Ready to be installed

No handles or tilt knobs to be fitted.

Lifting straps

For safe movement on site.







External Plant On Bar

For authentic appearance externally.

Packers

Available in PVC 15mm, 30mm or 50mm.

** Depending on Size/Weight of the Sash



Telephone: 01376 510 410 Fax: 01376 510 400

Masterframe Windows Ltd 4 Crittall Road, Witham, Essex, CM8 3DR Registered in England 2272659